

Pro XD Mid-Size Gas



ANSI/OPEI Certification

Polaris Industries Inc. certifies that these vehicles complies with the American National Standard for Multipurpose off-Highway Utility Vehicles, ANSI/OPEI B71.9 – 2016 Standard

Key Specifications

Gas	1,000	200-Hr
Fuel Type	lbs Payload	Maintenance Interval

Engine & Drivetrain

Air Intake	Side Air Intake
Cooling	Liquid
Cylinders Displacement	570 cc
Drive System Type	Selectable 4x4
Engine Type	ProStar 570 cc Gas
Fuel System/Battery	Electronic Fuel Injection
Horsepower	39.5 HP
Maintenance Interval	200 Hours (50 Hour initial)
Top Speed	Adjustable up to 40 mph (64 km/h)
Transmission/Final Drive	Automatic PVT H/L/N/R/P; Shaft

Dimensions

Bed Box Dimensions (L x W x H)	33.3" x 48.7" x 12.3" (84.6 x 123.7 x 31.2 cm)
Box Capacity	500 lb (226 kg)
Estimated Dry Weight	1,234 lb (560 kg)
Fuel Capacity	9.5 gal (36 L)
Ground Clearance	10 in (25.4 cm)
GVWR	2,255 lb (1023 kg)
Hitch Towing Rating	1,500 lb (680 kg)
Overall Vehicle Size (L x W x H)	108 x 56 x 74 in. (274.3 x 142.2 x 188 cm)
Payload Capacity	1,000 lb (453 kg)
Person Capacity	2

Turning Radius	152 in (386 cm)
Wheelbase	73 in (185.4 cm)

Brakes

Front/Rear Brakes	4-Wheel Hydraulic Disc
Parking Brake	Park in Transmission

Additional Specifications

Adjustable Driver Seat	Not Equipped
Cargo System	Lock & Ride®
Hitch Type	Standard 2 in (5 cm) Receiver
Instrumentation	All Digital Gauge, Speedometer, Odometer, Tachometer, 2 Tripmeters, Hour Meter, Gear Indicator, Diff Lock Indicator, Clock, Clutch Belt Slip Warning, Low Oil Pressure Indicator, Seat Belt Indicator
Lighting	55W Headlight, LED Taillamps
Other Standard Features	Horn, Backup Alarm, Password protected, electronically adjustable speed limiting
Seat Covering	Kevlar®-Backed Vinyl (Grey)
Tilt Steering	Standard

Tires / Wheels

Electronic Power Steering	Optional
Front Tires	25 x 9.00-12; Wanda Crawler P3057
Hubs	Front: Ductile Iron; Rear: Aluminum
Rear Tires	25 x 9.00-12 Wanda Crawler P3057
Wheels	12 x 6 HD Steel - Gloss Black

Suspension

Front Suspension	MacPherson Strut 9 in (22.9 cm) Travel
Rear Suspension	Dual A-Arm, IRS 10 in. (25.4 cm) Travel